



# E-Z MIX INC.

**PMP** PRE-MIX PRODUCTS

## ALPHA 800 (SC)

### PRODUCT

PMP ALPHA 800 (SC)

### DESCRIPTION

PMP ALPHA 800 (SC) is a temporary cold process asphalt patching material. It is designed to provide an economical yet effective temporary patch for holes in asphalt roads. PMP ALPHA 800 (SC) is not designed for areas which are exposed to foot traffic due to its prolonged tacky properties.

### USES

Temporary asphalt patch of:

- Potholes
- Utility Cuts
- Trenches

### ADVANTAGES

- Convenient 60 lb. bags
- Economical
- Saves labor
- Cleaner and easier handling

### PACKAGING

PMP ALPHA 800 (SC) is available in 60 lb. plastic bags. They are shipped as 50 bags per pallet.

### TECHNICAL DATA

PMP ALPHA 800 (SC) meets the requirements of section 203 Green Book (Standard Specifications for Public Works) and section 93 (Standard Specifications for Caltrans).

### COVERAGE

Each 60 lb. bag of PMP ALPHA 800 (SC) will fill an area of approximately 2.4 square feet at a 2" thickness.



### APPLICATIONS

For best results, clean all loose dirt and debris from in and around the hole. Fill holes in 2" lifts, thoroughly compacting each lift. Repaired areas should be filled approximately 1" - 2" above the surrounding surface to allow for further compaction. PMP ALPHA 800 (SC) is designed as a temporary patch and will remain soft and tacky for an extended period of time.

### LIMITATIONS

- Do not install in water
- Should be kept warm prior to installation

### WARRANTY

The technical information and usage statement are based on our best knowledge. The content of this specification sheet is presented for information purposes only and do not constitute responsibility for their use. The manufacturer will replace only that material which is proven defective due to quality of the components of the manufacturing process.

### CAUTION

Prolonged exposure to dust may cause delayed lung disease. Eliminate exposure to dust. Use NIOSH approved mask for silica dust. Freshly mixed material may cause skin irritation. Avoid direct contact when possible and wash exposed skin areas promptly with water and get prompt medical attention. See Safety Data Sheet.

For technical support contact:

[www.ezmixinc.com](http://www.ezmixinc.com)    [jjara@ezmixinc.com](mailto:jjara@ezmixinc.com)

**Corporate Office:**  
11374 Tuxford St.  
Sun Valley, CA 91352  
(818) 767-8576

**Sun Valley Plant:**  
11450 Tuxford St.  
Sun Valley, CA 91352  
(818) 768-0568

**Rialto Plant:**  
3355 Industrial Drive  
Rialto, CA 92316  
(909) 874-7686



**WARNING:** This product can expose you to chemicals including Chromium (hexavalent compounds), which are known to the state of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).