



12x6x16 Precision CMU




12x6x16 Standard

This item may be limited in plant location or color availability.




12x6x16 Bond Beam


This item may be limited in plant location or color availability.



12x6x16 Open End Standard




12x6x16 Open End Bond Beam




12x6x16 Double Open End Bond Beam

This item may be limited in plant location or color availability.



12x6x8 Half



12x6x8 U-Lintel

Features

6-inch high units provide a course height and face aspect that's just a little unusual; distinct from the ubiquitous standard 8-inch high masonry. Depending on context, the closer spacing of horizontal joints can evoke a bit more of a traditional feel, or work well in sleek modern designs.

Availability

Special order only. Units can be produced in any of our integral color options.

Standards

Concrete masonry units manufactured by Angelus Block Co., Inc. meet ASTM C90 Standard Specification for Loadbearing Concrete Masonry Units.

Fire Rating

Solid grouted walls 8-in wide and greater are rated at 4 hours, per CBC Table 721.1(2). For partially grouted walls, depending on the specified weight classification, 8-inch wide units are 1 hour to 2 hours, and 12-inch wide units are 2 hours to 3 hours.

Sustainable Features

- This product is included in Type III Environmental Product Declarations for Angelus Block Concrete Masonry Units, specific to location and mix designs, and in one of six *Health Product Declarations*, as applicable for its weight classification.
- Contributes to green rating systems calculations, including Regional Materials, EPDs, and Material Ingredient Reporting.
- Angelus Block CMU help facilitate and support many more strategies and credits, including Optimize Energy Performance, Construction Waste Management, and several within Indoor Environmental Quality. Angelus Block CMU contain no VOCs.

See *Sustainable & Resilient Design: Angelus Block Products' Application to Rating Systems and Code* for detailed information. A copy is available from your representative, or as a download at www.AngelusBlock.com.

Cells and web configurations as shown are representational only, and actual configurations may differ.

Corporate Office & Plants:

11374 Tuxford St. Orange, CA
Sun Valley, CA 91352 Fontana, CA
(818) 767-8576 Gardena, CA

Oxnard, CA
Indio, CA
Bakersfield, CA

www.AngelusBlock.com

info@AngelusBlock.com



This is a low impact CarbonKind™ product which substantially reduces CO₂e. Learn more at Angelus Block/CarbonKind.



WARNING: This product can expose you to Silica, crystalline (airborne particles of respirable size) which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov.