




# 12x6x16 Slumpstone™ CMU




**12x6x16 Standard**




**12x6x16 Bond Beam**  
Mixed with Standard. Special order if separate.



**12x6x16 Open End Standard**  
Open end legs subject to variations from overall unit width.



**12x6x16 Open End Bond Beam**  
Open end legs subject to variations from overall unit width.



**12x6x8 Half**

## Features

Slumpstone units feature irregularly rounded or bulged surfaces with a texture ranging from slick to coarse, providing a warm, rustic appearance.

## Availability

**Special order only.** Units can be produced in any of our Slumpstone integral color options on special order.

## Standards

Concrete masonry units manufactured by Angelus Block Co., Inc. meet ASTM C90 Standard Specification for Loadbearing Concrete Masonry Units.

## Fire Rating

Solid grouted walls 8-in wide and greater are rated at 4 hours, per CBC Table 721.1(2). For partially grouted walls, depending on the specified weight classification, 8-inch wide units are 1 hour to 2 hours, and 12-inch wide units are 2 hours to 3 hours.

## Sustainable Features

- This product is included in Type III Environmental Product Declarations for Angelus Block Concrete Masonry Units, specific to location and mix designs, and in one of six *Health Product Declarations*, as applicable for its weight classification.
- Contributes to green rating systems calculations, including Regional Materials, EPDs, and Material Ingredient Reporting.
- Angelus Block CMU help facilitate and support many more strategies and credits, including Optimize Energy Performance, Construction Waste Management, and several within Indoor Environmental Quality. Angelus Block CMU contain no VOCs.

See *Sustainable & Resilient Design: Angelus Block Products' Application to Rating Systems and Code* for detailed information. A copy is available from your representative, or as a download at [www.AngelusBlock.com](http://www.AngelusBlock.com).

Cells and web configurations as shown are representational only, and actual configurations may differ.

**Corporate Office & Plants:**

11374 Tuxford St.      Orange, CA  
Sun Valley, CA 91352      Fontana, CA  
(818) 767-8576      Gardena, CA

Oxnard, CA  
Indio, CA  
Bakersfield, CA

[www.AngelusBlock.com](http://www.AngelusBlock.com)

[info@AngelusBlock.com](mailto:info@AngelusBlock.com)



This is a low impact CarbonKind™ product which substantially reduces CO<sub>2</sub>e. Learn more at Angelus Block/CarbonKind.



**WARNING:** This product can expose you to Silica, crystalline (airborne particles of respirable size) which is known to the State of California to cause cancer. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).