



# 6x6x16 Shotblast CMU



**6x6x16  
Standard**



**6x6x8  
Half**

## Features

6-inch high units provide a course height and face aspect that's just a little unusual; distinct from the ubiquitous standard 8-inch high masonry. Depending on context, the closer spacing of horizontal joints can evoke a bit more of a traditional feel, or work well in sleek modern designs.

## Availability

**Special order.** Configurations such as open ends, bond beams, open end bond beams and Shotblast on multiple faces may be available. Units can be made in any of our integral color options.

## Standards

Concrete masonry units manufactured by Angelus Block Co., Inc. meet ASTM C90 Standard Specification for Loadbearing Concrete Masonry Units.

## Fire Rating

Solid grouted walls 8-in wide and greater are rated at 4 hours, per CBC Table 721.1(2). For partially grouted walls, depending on the specified weight classification, 8-inch wide units are 1 hour to 2 hours, and 12-inch wide units are 2 hours to 3 hours.

## Sustainable Features

- This product is included in Type III Environmental Product Declarations for Angelus Block Concrete Masonry Units, specific to location and mix designs, and in one of six *Health Product Declarations*, as applicable for its weight classification.
- Contributes to green rating systems calculations, including Regional Materials, EPDs, and Material Ingredient Reporting.
- Angelus Block CMU help facilitate and support many more strategies and credits, including Optimize Energy Performance, Construction Waste Management, and several within Indoor Environmental Quality. Angelus Block CMU contain no VOCs.

See *Sustainable & Resilient Design: Angelus Block Products' Application to Rating Systems and Code* for detailed information. A copy is available from your representative, or as a download at [www.AngelusBlock.com](http://www.AngelusBlock.com).

Degree of texturing of Shotblast units will vary from unit to unit.

Cells and web configurations as shown are representational only, and actual configurations may differ.

**Corporate Office & Plants:**

11374 Tuxford St.      Orange, CA  
Sun Valley, CA 91352      Fontana, CA  
(818) 767-8576      Gardena, CA

Oxnard, CA  
Indio, CA  
Bakersfield, CA

[www.AngelusBlock.com](http://www.AngelusBlock.com)

[info@AngelusBlock.com](mailto:info@AngelusBlock.com)



This is a low impact CarbonKind™ product which substantially reduces CO<sub>2</sub>e. Learn more at Angelus Block/CarbonKind.



**WARNING:** This product can expose you to Silica, crystalline (airborne particles of respirable size) which is known to the State of California to cause cancer. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).