




8x4x16 Burnished CMU




**8x4x16
Standard**




**8x4x16
Bond Beam**




**8x4x16
Open End Standard**



**8x4x16
Open End Bond Beam**



**8x4x8
Half**



**8x4x8
U-Lintel**

Features

When used as a field, the course module of 4-inch high cmu creates a more traditional scale, expressing the warmth of historical masonry. 4-high units are also effective as banding elements to add sightlines and interest to large elevations. Burnishing reveals the aggregate matrix for a rich, natural, yet refined look.

Availability

Special order. Burnish on multiple sides is available. Units can be made in any of our integral color op

Standards

Concrete masonry units manufactured by Angelus Block Co., Inc. meet ASTM C90 Standard Specification for Loadbearing Concrete Masonry Units.

Fire Rating

Solid grouted walls 8-in wide and greater are rated at 4 hours, per CBC Table 721.1(2). For partially grouted walls, depending on the specified weight classification, 8-inch wide units are 1 hour to 2 hours, and 12-inch wide units are 2 hours to 3 hours.

Sustainable Features

- This product is included in Type III Environmental Product Declarations for Angelus Block Concrete Masonry Units, specific to location and mix designs, and in one of six *Health Product Declarations*, as applicable for its weight classification.
- Contributes to green rating systems calculations, including Regional Materials, EPDs, and Material Ingredient Reporting.
- Angelus Block CMU help facilitate and support many more strategies and credits, including Optimize Energy Performance, Construction Waste Management, and several within Indoor Environmental Quality. Angelus Block CMU contain no VOCs.

See *Sustainable & Resilient Design: Angelus Block Products' Application to Rating Systems and Code* for detailed information. A copy is available from your representative, or as a download at www.AngelusBlock.com.

ions.

Aggregate exposure in all Burnished units will vary across the unit face, and from unit to unit.

Cells and web configurations as shown are representational only, and actual configurations may differ.

Corporate Office & Plants:

11374 Tuxford St. Orange, CA
Sun Valley, CA 91352 Fontana, CA
(818) 767-8576 Gardena, CA

Oxnard, CA
Indio, CA
Bakersfield, CA

www.AngelusBlock.com

info@AngelusBlock.com



This is a low impact CarbonKind™ product which substantially reduces CO₂e. Learn more at AngelusBlock/CarbonKind.



WARNING: This product can expose you to Silica, crystalline (airborne particles of respirable size) which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov.