



# 8x8x16 Burnished CMU


**CONCRETE MASONRY UNITS**




**8x8x16  
Standard**




**8x8x16  
Bond Beam**




**8x8x16  
Open End Standard**




**8x8x16  
Open End Bond Beam**




**8x8x16  
Double Open End Bond Beam**




**8x8x8  
Half**



**8x8x8  
U-Lintel**



**8x8x16  
Solid Bottom U-Lintel**



**8x8x16  
No Center Web**

**Availability**

Special order only. Burnishing on multiple faces is available. Units may be made in any of our integral color options.

**Standards**

Concrete masonry units manufactured by Angelus Block Co., Inc. meet ASTM C90 Standard Specification for Loadbearing Concrete Masonry Units.

**Fire Rating**

Solid grouted walls 8-in wide and greater are rated at 4 hours, per CBC Table 721.1(2). For partially grouted walls, depending on the specified weight classification, 8-inch wide units are 1 hour to 2 hours, and 12-inch wide units are 2 hours to 3 hours.

**Sustainable Features**

- This product is included in Type III Environmental Product Declarations for Angelus Block Concrete Masonry Units, specific to location and mix designs, and in one of six *Health Product Declarations*, as applicable for its weight classification.
- Contributes to green rating systems calculations, including Regional Materials, EPDs, and Material Ingredient Reporting.
- Angelus Block CMU help facilitate and support many more strategies and credits, including Optimize Energy Performance, Construction Waste Management, and several within Indoor Environmental Quality. Angelus Block CMU contain no VOCs.

See *Sustainable & Resilient Design: Angelus Block Products' Application to Rating Systems and Code* for detailed information. A copy is available from your representative, or as a download at [www.AngelusBlock.com](http://www.AngelusBlock.com).

Aggregate exposure in all Burnished units will vary across the unit face, and from unit to unit.

Cells and web configurations as shown are representational only, and actual configurations may differ.

Corporate Office & Plants:

11374 Tuxford St.      Orange, CA  
Sun Valley, CA 91352      Fontana, CA  
(818) 767-8576      Gardena, CA

Oxnard, CA  
Indio, CA  
Bakersfield, CA

[www.AngelusBlock.com](http://www.AngelusBlock.com)

[info@AngelusBlock.com](mailto:info@AngelusBlock.com)



This is a low impact CarbonKind™ product which substantially reduces CO<sub>2</sub>e. Learn more at Angelus Block/CarbonKind.