Veneer / Composite CMU
Shotblast

15 5/8

3 5/8

2 5/8

**3x4x16
Solid**

15 5/8

5 5/8

2 13/16

**3x6x16
Solid**

15 5/8

7 5/8

2 5/8

**3x8x16
Solid**

15 5/8

3 5/8

3 5/8

**4x4x16
Solid**

15 5/8

7 5/8

3 5/8

**4x8x16
Solid**

Degree of texturing of Shotblast units will vary from unit to unit.

Features

These units are suitable for use in anchored veneer or composite masonry applications.

The Shotblast texture roughens the surface and removes sharp edges.

For veneer masonry: Use in anchored veneer applications per TMS 402 Chapter 12 and TMS 602.

For composite masonry: Use in multiwythe masonry per CBC and TMS 402 and TMS 602.

Availability

Special order only. Available in any of our integral color options.

Standards

Concrete masonry units manufactured by Angelus Block Co., Inc. meet ASTM C90 Standard Specification for Loadbearing Concrete Masonry Units.

Sustainable Features

- This product is included in Type III Environmental Product Declarations for Angelus Block Concrete Masonry Units, specific to location and mix designs, and in one of six *Health Product Declarations*, as applicable for its weight classification.

- Contributes to green rating systems calculations, including Regional Materials, EPDs, and Material Ingredient Reporting.

- Angelus Block CMU help facilitate and support many more strategies and credits, including Optimize Energy Performance, Construction Waste Management, and several within Indoor Environmental Quality. Angelus Block CMU contain no VOCs.

  See *Sustainable & Resilient Design: Angelus Block Products' Application to Rating Systems and Code* for detailed information. A copy is available from your representative, or as a download at www.AngelusBlock.com.

CarbonKind™
by Angelus Block

This is a low impact CarbonKind™ product which substantially reduces CO_2e. Learn more at Angelus Block/CarbonKind.