

Product Data Sheet

12 Silver Sand

*In compliance with ANSI/NSF 61 for water filtration
California ARB certified for outdoor sandblasting*

Typical Physical Properties

Color:	Light tan
Grain Shape:	Sub-angular
Hardness, Moh	6.5
Moisture Content(% by wt):	< 0.1
Bulk Density :	94 lbs/ft ³ (1500 kg/m ³)
Specific Gravity:	2.60
Effective Size:	1.20-1.40
Uniformity Coefficient:	1.35-1.55

Typical Sieve Analysis

US Sieve Size No.	% Retained on Sieve	Range
8	2	0-5
10	20	10-35
12	52	40-65
16	22	10-40
20	2	0-5
30	1	0-2

DISCLAIMER:

The information presented in this Product Data Sheet lists typical properties of the described product. By this Product Data Sheet, P.W. Gillibrand Co., Inc. makes no warranty, expressed or implied, of fitness for any purpose.

WARNING:

This product contains crystalline silica (Quartz), known to the State of California to cause cancer. For additional information on the potential health effects of crystalline silica, please see the P.W. Gillibrand Co., Inc. Material Safety Data Sheet (MSDS).

PO. Box 1019. 4537 Ish Drive, Simi Valley, CA 93062-1019 Ph: 805 526 2195 Fax: 805 522 4031

www.pwgillibrand.com