



E-Z MIX INC.

PMP PRE-MIX PRODUCTS

SPEC CONCRETE 3000

for use in *poured-in-place* applications

PRODUCT

PMP Spec Concrete 3000

DESCRIPTION

PMP Spec Concrete 3000 is a dry, factory blended concrete mix specifically designed for the professional contractor. The proportioning of raw materials and the thorough blending of the product make it superior to the conventional sacked concrete products. Standard mix is 6.5 sack, 70% sand and 30% 3/8" aggregate.

USES

PMP Spec Concrete 3000 may be used where a 3000-psi concrete is specified.

ADVANTAGES

- High Quality
- Convenience of handling one product
- Excellent for multistory and difficult access jobs
- Systems that save time and money on labor
- Meets building code requirements

PACKAGING

Available in 90 lb. multiwall paper bags, 3000 lb. bulk bags and bulk. Information on silo and bulk systems available upon request.

COVERAGE

One 90 lb. bag will yield approximately 0.70 cubic feet.

TECHNICAL DATA

PMP Spec Concrete 3000 is proportioned in accordance with and meets the performance specifications of current edition of ASTM C387 Standard Specification for Packaged, Dry, Combined Materials for Concrete and High Strength Mortar. PMP Spec Concrete 3000 is **City of Los Angeles Approved RR 24968**. PMP Spec Concrete 3000 is blended with Type II/V Portland Cement and washed aggregates to applicable ASTM standards.



APPLICATION

FOR USE IN PORED-IN-PLACE CONCRETE APPLICATIONS. Add PMP Spec Concrete 3000 to clean potable water and mix to achieve a 2"-3" slump. One 90 lb. bag will yield approximately .66 cubic feet.

WARRANTY

The technical information and usage statement are based on our best knowledge. The content of this specification sheet is presented for information purposes only and do not constitute responsibility for their use. The manufacturer will replace only that material which is proven defective due to quality of the components of the manufacturing process.

CAUTION

Prolonged exposure to dust may cause delayed lung disease. Eliminate exposure to dust. Use NIOSH approved mask for silica dust. Freshly mixed material may cause skin irritation. Avoid direct contact when possible and wash exposed skin areas promptly with water and get prompt medical attention. See Safety Data Sheet.

For technical support contact:

www.ezmixinc.com jjara@ezmixinc.com

Corporate Office:
11374 Tuxford St.
Sun Valley, CA 91352
(818) 767-8576

Rialto Plant:
3355 Industrial Drive
Rialto, CA 92316
(909) 874-7686

Sun Valley Plant:
11450 Tuxford St.
Sun Valley, CA 91352
(818) 768-0568



WARNING: This product can expose you to chemicals including Chromium (hexavalent compounds), which are known to the state of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.